




**KWLT30-HL-V1-G3** [↗](#)

Recirculating ball bearing carriage

Long & high carriage, standard end plate, for four-row linear recirculating ball bearing and guideway assembly

Technical information

**Your current product variant**

Size code	30	
Carriage design	HL	High, long design
Preload	V1	Slight preload (standard)
Accuracy class	G3	

Main Dimensions & Performance Data

H	45 mm	Height system
B	60 mm	Width carriage
L	125,4 mm	Overall length carriage
C	34.000 N	Dynamic load rating
C ₀	66.000 N	Basic static load capacity
M _{0x}	1.060 Nm	Static moment rating about X-axis
M _{0y}	940 Nm	Static moment rating about Y-axis
M _{0z}	940 Nm	Static moment rating about Z-axis
M _{0x}	495 Nm	Dynamic moment rating about X-axis
M _{0y}	810 Nm	Dynamic moment rating about y-axis
M _{0z}	810 Nm	Dynamic moment rating about Z-axis
≈m	1,13 kg	Weight



Mounting dimensions

A ₁	16 mm	Distance from locating edge on carriage to locating edge on guideway
A ₂	10 mm	Distance from locating edge to hole
L ₁	92,4 mm	Carrier length
H ₁	9 mm	Free space, system dimension
J _B	40 mm	Hole spacing
J _L	60 mm	Hole Spacing
A ₃	11 mm	Position lubrication connector
T ₅	11 mm	Thread depth
G ₂	M8	Thread size, DIN ISO 4762-12.9
G2 M _A	40 Nm	Maximum tightening torque

Additional information

VMKB_065	KWLT	Material name
----------	------	---------------