

**KWL15-H-V0-G4** [↗](#)

## Recirculating ball bearing carriage

High carriage, standard end plate, for four-row linear recirculating ball bearing and guideway assembly

## Technical information

**Your current product variant**

Size Code	15	
Carriage design	H	High design
Preload	V0	Slight clearance
Accuracy class	G4	

**Main Dimensions & Performance Data**

H	28 mm	Height system
B	34 mm	Width carriage
L	62 mm	Overall length carriage
C	8.400 N	Dynamic load rating
C <sub>0</sub>	16.200 N	Basic static load capacity
M <sub>0x</sub>	140 Nm	Static moment rating about X-axis
M <sub>0y</sub>	99 Nm	Static moment rating about Y-axis
M <sub>0z</sub>	99 Nm	Static moment rating about Z-axis
M <sub>0x</sub>	65 Nm	Dynamic moment rating about X-axis
M <sub>0y</sub>	85 Nm	Dynamic moment rating about y-axis
M <sub>0z</sub>	85 Nm	Dynamic moment rating about Z-axis
≈m	190 g	Weight



### Mounting dimensions

---

A <sub>1</sub>	9,5 mm	Distance from locating edge on carriage to locating edge on guideway
A <sub>2</sub>	4 mm	Distance from locating edge to hole
L <sub>1</sub>	40 mm	Carrier length
H <sub>1</sub>	4,6 mm	Free space, system dimension
J <sub>B</sub>	26 mm	Hole spacing
J <sub>L</sub>	26 mm	Hole Spacing
A <sub>3</sub>	8,3 mm	Position lubrication connector
T <sub>5</sub>	7,5 mm	Thread depth
G <sub>2</sub>	M4	Thread size, DIN ISO 4762-12.9
G2 M <sub>A</sub>	4,95 Nm	Maximum tightening torque

### Additional information

---

VMKB_065	KWLT	Material name
----------	------	---------------