

**KWLT30-SL-V0-G3**

Recirculating ball bearing carriage

Long & slim carriage, standard end plate, for four-row linear recirculating ball bearing and guideway assembly

Technical information

**Your current product variant**

Size code	30	
Carriage design	SL	Narrow, long design
Preload	V0	Slight clearance
Accuracy class	G3	

Main Dimensions & Performance Data

H	42 mm	Height system
B	60 mm	Width carriage
L	125,4 mm	Overall length carriage
C	34.000 N	Dynamic load rating
C ₀	66.000 N	Basic static load capacity
M _{0x}	1.060 Nm	Static moment rating about X-axis
M _{0y}	940 Nm	Static moment rating about Y-axis
M _{0z}	940 Nm	Static moment rating about Z-axis
M _{0x}	495 Nm	Dynamic moment rating about X-axis
M _{0y}	810 Nm	Dynamic moment rating about y-axis
M _{0z}	810 Nm	Dynamic moment rating about Z-axis
m	1,01 kg	Weight



Mounting dimensions

A ₁	16 mm	Distance from locating edge on carriage to locating edge on guideway
A ₂	10 mm	Distance from locating edge to hole
L ₁	92,4 mm	Carrier length
H ₁	9 mm	Free space, system dimension
J _B	40 mm	Hole spacing
J _L	60 mm	Hole Spacing
A ₃	8 mm	Position lubrication connector
T ₅	8,5 mm	Thread depth
G ₂	M8	Thread size, DIN ISO 4762-12.9
G2 M _A	40 Nm	Maximum tightening torque

Additional information

VMKB_065	KWLT	Material name
----------	------	---------------