

**KWLT20-SL-V2-G4**

## Recirculating ball bearing carriage

Long & slim carriage, standard end plate, for four-row linear recirculating ball bearing and guideway assembly



## Technical information

**Your current product variant**

Size Code	20	
Carriage design	SL	Narrow, long design
Preload	V2	Preload class 2
Accuracy class	G4	

**Main Dimensions & Performance Data**

H	30 mm	Height system
B	44 mm	Width carriage
L	88 mm	Overall length carriage
C	15.100 N	Dynamic load rating
C <sub>0</sub>	30.000 N	Basic static load capacity
M <sub>0x</sub>	325 Nm	Static moment rating about X-axis
M <sub>0y</sub>	300 Nm	Static moment rating about Y-axis
M <sub>0z</sub>	300 Nm	Static moment rating about Z-axis
M <sub>0x</sub>	148 Nm	Dynamic moment rating about X-axis
M <sub>0y</sub>	251 Nm	Dynamic moment rating about y-axis
M <sub>0z</sub>	251 Nm	Dynamic moment rating about Z-axis
≈m	400 g	Weight



### Mounting dimensions

A <sub>1</sub>	12 mm	Distance from locating edge on carriage to locating edge on guideway
A <sub>2</sub>	6 mm	Distance from locating edge to hole
L <sub>1</sub>	66,2 mm	Carrier length
H <sub>1</sub>	5 mm	Free space, system dimension
J <sub>B</sub>	32 mm	Hole spacing
J <sub>L</sub>	50 mm	Hole Spacing
A <sub>3</sub>	5,7 mm	Position lubrication connector
T <sub>5</sub>	6,5 mm	Thread depth
G <sub>2</sub>	M5	Thread size, DIN ISO 4762-12.9
G2 M <sub>A</sub>	9,7 Nm	Maximum tightening torque

### Additional information

VMKB_065	KWLT	Material name
----------	------	---------------