

**FAG****61816-C3**

Deep groove ball bearing

Deep groove ball bearing 618, single row,
steel sheet metal cage

Technical information

**Your current product variant**

Type of Seal	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	80 mm	Bore diameter
D	100 mm	Outside diameter
B	10 mm	Width
C_r	13.800 N	Basic dynamic load rating, radial
C_{0r}	13.800 N	Basic static load rating, radial
C_{ur}	930 N	Fatigue load limit, radial
n_G	9.400 1/min	Limiting speed
n_{gr}	4.600 1/min	Reference speed
m	0,157 kg	Weight



Mounting dimensions

$d_{a \min}$	83,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	96,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,6 mm	Maximum fillet radius

Dimensions

r_{\min}	0,6 mm	Minimum chamfer dimension
D_1	93,57 mm	Shoulder diameter outer ring
d_1	86,6 mm	Shoulder diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Calculation factors

f_0	16	Calculation factor
-------	----	--------------------

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed