

**FAG****S626-2Z>N**

Deep groove ball bearing

Deep groove ball bearing S62...-2Z, corrosion-resistant materials, single row, shields, steel sheet metal cage

Technical information



Your current product variant

Version code	>N	Not marked on bearing
Material Bearing	S	Stainless steel
Sealing	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Lubricating grease	
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	6 mm	Bore diameter
D	19 mm	Outside diameter
B	6 mm	Width
C_r	2.360 N	Basic dynamic load rating, radial
C_{0r}	890 N	Basic static load rating, radial
C_{ur}	55 N	Fatigue load limit, radial
n_G	47.000 1/min	Limiting speed
n_{gr}	32.500 1/min	Reference speed
$\approx m$	8,65 g	Weight



Mounting dimensions

$d_{a \min}$	8,4 mm	Minimum diameter shaft shoulder
$D_{a \max}$	16,6 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,3 mm	Maximum fillet radius

Dimensions

r_{\min}	0,3 mm	Minimum chamfer dimension
D_1	14,9 mm	Shoulder diameter outer ring
D_2	16,1 mm	Caliber diameter outer ring
d_1	10,2 mm	Shoulder diameter inner ring
d_2	9 mm	Caliber diameter inner ring








Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Calculation factors

f_0	12,6	Calculation factor
-------	------	--------------------

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides
	Protected against rust