

**FAG****S693>N**

Deep groove ball bearing

Deep groove ball bearing S69, corrosion-resistant materials, single row, steel sheet metal cage

Technical information



Your current product variant

Version code	>N	Not marked on bearing
Material Bearing	S	Stainless steel
Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	3 mm	Bore diameter
D	8 mm	Outside diameter
B	3 mm	Width
C _r	590 N	Basic dynamic load rating, radial
C _{0r}	180 N	Basic static load rating, radial
C _{ur}	11,1 N	Fatigue load limit, radial
n _G	102.000 1/min	Limiting speed
n _{gr}	54.000 1/min	Reference speed
m	0,6 g	Weight



Mounting dimensions

$d_{a \min}$	3,8 mm	Minimum diameter shaft shoulder
$D_{a \max}$	7,2 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,15 mm	Maximum fillet radius

Dimensions

r_{\min}	0,15 mm	Minimum chamfer dimension
D_1	6,7 mm	Shoulder diameter outer ring
d_1	5,3 mm	Shoulder diameter inner ring








Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Calculation factors

f_0	11,9	Calculation factor
-------	------	--------------------

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Protected against rust