

**FAG****S6201>N**

Deep groove ball bearing

Deep groove ball bearing S62, corrosion-resistant materials, single row, steel sheet metal cage

Technical information



Your current product variant

Version code	>N	Not marked on bearing
Material Bearing	S	Stainless steel
Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	12 mm	Bore diameter
D	32 mm	Outside diameter
B	10 mm	Width
C _r	7.200 N	Basic dynamic load rating, radial
C _{0r}	3.050 N	Basic static load rating, radial
C _{ur}	189 N	Fatigue load limit, radial
n _G	33.500 1/min	Limiting speed
n _{gr}	22.200 1/min	Reference speed
m	38 g	Weight



Mounting dimensions

$d_{a \min}$	16,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	27,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,6 mm	Maximum fillet radius

Dimensions

r_{\min}	0,6 mm	Minimum chamfer dimension
D_1	25,9 mm	Shoulder diameter outer ring
D_2	27,6 mm	Caliber diameter outer ring
d_1	18,1 mm	Shoulder diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Calculation factors

f_0	12,3	Calculation factor
-------	------	--------------------

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Protected against rust