



NSHS-206 [↗](#)

Hydraulic cylinder, 700 bar

BETEX NSHS Hollow-piston cylinder, single-acting, spring return, 20T class

Technical information



Your current product variant

Series	NSHS	Hollow piston cylinder
Version	20T	Capacity class 20



Technical data

	20	Capacity class (tons)
s _p	155 mm	Stroke
A _p	34 cm ²	Effective piston area
F _a	238 kN	Advance force, max.
P _{max}	700 bar	Operating pressure, max.
V _{oil}	527 cm ³	Oil capacity
A	306 mm	Height, retracted
B	461 mm	Height, extended
D	98,5 mm	Outer diameter
E	75 mm	Cylinder bore diameter
F	55 mm	Plunger diameter
H	19 mm	Base to advance port
J	54 mm	Saddle diameter
K	7 mm	Saddle protrusion from plunger
O	1 9/16"-16 UN	Plunger female thread (UN)
P	25 mm	Plunger thread length
U	82,6 mm	Base mounting holes, bolt circle
V	3/8"-16 UN	Base mounting holes, thread (UNC)
Z	9,4 mm	Base mounting holes, thread depth
W	3/8"-12 UN	Collar thread (UN)
X	38 mm	Collar thread, length
Y	27 mm	Center hole diameter
≈m	13,5 kg	Weight

Additional information

Hard chrome plated and hardened piston,
Rolled inside of cylinder,
Sandblasted outside
with black nitride coating,
Coupling with dust cap

Product specifics