

**GAKSL20-PS** [↗](#)

Rod end

Corrosion-resistant rod end, with external thread, maintenance-free, sliding layer: PTFE film, DIN ISO 12240-4, dimension series K, type F, open design

Technical information



Your current product variant

Clampable	Not clampable
Mounting	External thread
Grease nipples	Cannot be relubricated
Slotted	No
Thread Pitch	Left-hand thread
Maintenance	Maintenance free
Sealing	Without
Material sliding Layer	Sliding foil

Main Dimensions & Performance Data

d_2	51 mm	Outer diameter eye
C_r	57.000 N	Basic dynamic load rating
C_{0r}	22.800 N	Basic static load rating
d	20 mm	Bore diameter bearing
D	40 mm	Outside diameter bearing
l_2	104 mm	Total length
B	25 mm	Width inner ring
$\approx m$	0,355 kg	Weight



Dimensions

d_k	34,9 mm	Ball diameter
d_1	24,4 mm	Outer flange diameter inner ring
d_3	M20X1,5	Thread size
h	78 mm	Length of thread
C_1	18 mm	Width of the rod end
α	15 °	Tilt angle
l_1	45 mm	Thread length
l_7	25 mm	Length of the flat surface from the bearing bore centre to the shank
B_{UT}	-0,12 mm	Width inner ring , lower tolerance
B_{OT}	0 mm	Width inner ring; upper tolerance
d_T	H7	Bore diameter_bearing_tolerance
d_{UT}	0 mm	Bore diameter, lower tolerance
d_{OT}	0,021 mm	Bore diameter bearing upper tolerance
G_r	0,010 - 0,055	Radial clearance
G_{rmax}	0,055 mm	Radial clearance, maximum
G_{rmin}	0,01 mm	Radial clearance, minimum

Temperature range

T_{min}	-10 °C	Operating temperature min.
T_{max}	80 °C	Operating temperature max.

Mounting dimensions

r_{1s}	0,3 mm	Smallest single chamfer dimension, inner ring
----------	--------	---



Characteristics



Radial load



Lifetime lubrication, freedom from maintenance



Not sealed



Protected against rust



Static angular error and misalignment



Dynamic angular error and misalignment