

**GIKR12-PW**

Rod end

Rod end with internal thread, right hand thread, maintenance-free, sliding layer: PTFE film, brass outer ring, DIN ISO 12240-4, dimension series K, type F, open design

Technical information



Your current product variant

Clampable	Not clampable
Maintenance	Maintenance free
Mounting	Internal thread
Lubrication nipple	Cannot be relubricated
Slotted	No
Thread Pitch	Right-hand thread
Type of Sealing	Without

Main Dimensions & Performance Data

C_r	24.000 N	Basic dynamic load rating, radial
C_{0r}	20.800 N	Basic static load rating, radial
d	12 mm	Bore diameter bearing
d_2	32 mm	Outer eye diameter
l_4	66 mm	Total length internal thread head
$\approx m$	0,12 kg	Weight



Dimensions

C ₁	12 mm	Width of the rod end
D	26 mm	Outside diameter bearing
B	16 mm	Width inner ring
d _K	22,225 mm	Ball diameter
d ₃	M12	Thread size
d ₄	17,5 mm	Shank diameter
d ₅	22 mm	Shank diameter, large
h ₁	50 mm	Shank Length Internal thread head
α	13 °	Tilt angle
l ₃	22 mm	Thread length Internal thread
l ₅	6,5 mm	Length rod end shank
l ₇	17 mm	Distance drilling with/shaft start
W	19 mm	Width Across Flat
d _{UT}	0 mm	Bore diameter bearing, lower tolerance
d _T	H7	Bore diameter bearing, tolerance
d _{OT}	0,018 mm	Bore diameter bearing, upper tolerance
B _{UT}	-0,12 mm	Width inner ring, lower tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
G _r	0 - 0,035	Radial Clearance
G _{rmin}	0 mm	Radial clearance, minimum
G _{rmax}	0,035 mm	Radial clearance, maximum

Mounting dimensions

r _{1smin}	0,3 mm	Edge Spacing
d ₁	15,4 mm	Outer flange diameter inner ring



Temperature range

T_{\min}	-50 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Characteristics

-  F_r Radial load
-  L_h Lifetime lubrication, freedom from maintenance
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment