


**GAL6-DO**

## Rod end



Rod end with external thread, left hand thread, requiring maintenance, sliding contact surface: steel/steel, DIN ISO 12240-4, dimension series E, type M, open

## Technical information



## Your current product variant

Clampable	Not clampable	
Maintenance	Maintenance required	
Lubrication nipple	Cannot be relubricated	
Slotted	No	
Thread Pitch	Left-hand thread	
Sealing	Without	
Radial internal clearance	CN (Group N)	Normal internal clearance
Mounting	External thread	

## Main Dimensions &amp; Performance Data

$C_r$	4.420 N	Basic dynamic load rating, radial
$C_{0r}$	6.930 N	Basic static load rating, radial
d	6 mm	Bore diameter bearing
D	14 mm	Outside diameter bearing
$l_2$	46,5 mm	Total length external thread head
B	6 mm	Width inner ring
$d_2$	21 mm	Outer eye diameter
$\approx m$	18 g	Weight



### Mounting dimensions

d <sub>1</sub>	8 mm	Outer flange diameter inner ring
r <sub>1smin</sub>	0,3 mm	Edge Spacing

### Dimensions

d <sub>K</sub>	10 mm	Ball diameter
d <sub>3</sub>	M6	Thread size
h	36 mm	Shank Length External thread rod
C <sub>1</sub>	4,4 mm	Width of the rod end
α	13 °	Tilt angle
l <sub>1</sub>	18 mm	Shank Length External thread head
l <sub>7</sub>	12 mm	Distance drilling with/shaft start
d <sub>OT</sub>	0 mm	Bore diameter bearing, upper tolerance
d <sub>UT</sub>	-0,008 mm	Bore diameter bearing, lower tolerance
B <sub>OT</sub>	0 mm	Width inner ring, upper tolerance
B <sub>UT</sub>	-0,12 mm	Width inner ring, lower tolerance
G <sub>r</sub>	0,023 - 0,068	Radial Clearance
G <sub>rmax</sub>	0,068 mm	Radial clearance, maximum
G <sub>rmin</sub>	0,023 mm	Radial clearance, minimum

### Temperature range

T <sub>min</sub>	-60 °C	Operating temperature min.
T <sub>max</sub>	200 °C	Operating temperature max.



## Characteristics

---



Radial load



Grease Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment