


**GAR25-DO**

## Rod end



Rod end with external thread, right hand thread, requiring maintenance, sliding contact surface: steel/steel, DIN ISO 12240-4, dimension series E, type M, open

## Technical information



## Your current product variant

Clampable	Not clampable
Maintenance	Maintenance required
Mounting	External thread
Lubrication nipple	DIN71412-AS6 (tapered grease nipple)
Slotted	No
Thread Pitch	Right-hand thread
Type of Sealing	Without
Radial internal clearance	CN (Group N)      Normal internal clearance

## Main Dimensions &amp; Performance Data

$C_r$	62.800 N	Basic dynamic load rating, radial
$C_{0r}$	88.300 N	Basic static load rating, radial
d	25 mm	Bore diameter bearing
D	42 mm	Outside diameter bearing
$l_2$	126 mm	Total length external thread head
B	20 mm	Width inner ring
$d_2$	64 mm	Outer eye diameter
$\approx m$	0,569 kg	Weight



### Mounting dimensions

d <sub>1</sub>	29,3 mm	Outer flange diameter inner ring
r <sub>1smin</sub>	0,6 mm	Edge Spacing

### Dimensions

d <sub>K</sub>	35,5 mm	Ball diameter
d <sub>3</sub>	M24x2	Thread size
h	94 mm	Shank Length External thread rod
C <sub>1</sub>	17 mm	Width of the rod end
α	7 °	Tilt angle
l <sub>1</sub>	53 mm	Shank Length External thread head
l <sub>7</sub>	32 mm	Distance drilling with/shaft start
d <sub>OT</sub>	0 mm	Bore diameter bearing, upper tolerance
d <sub>UT</sub>	-0,01 mm	Bore diameter bearing, lower tolerance
B <sub>OT</sub>	0 mm	Width inner ring, upper tolerance
B <sub>UT</sub>	-0,12 mm	Width inner ring, lower tolerance
G <sub>r</sub>	0,037 - 0,1	Radial Clearance
G <sub>rmax</sub>	0,1 mm	Radial clearance, maximum
G <sub>rmin</sub>	0,037 mm	Radial clearance, minimum

### Temperature range

T <sub>min</sub>	-60 °C	Operating temperature min.
T <sub>max</sub>	200 °C	Operating temperature max.



### Characteristics

---



Radial load



Grease Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment