

**GIKL20-PB** [↗](#)

## Rod end



Rod end with internal thread, left hand thread,  
requiring maintenance, DIN ISO 12240-4.  
dimension series K, type F, open design

## Technical information



## Your current product variant

Clampable	Not clampable
Maintenance	Maintenance required
Lubrication nipple	DIN71412-AS6 (tapered grease nipple)
Slotted	No
Thread Pitch	Left-hand thread
Sealing	Without
Mounting	Internal thread

## Main Dimensions &amp; Performance Data

d	20 mm	Bore diameter bearing
D	40 mm	Outside diameter bearing
B	25 mm	Width inner ring
C <sub>r</sub>	31.400 N	Basic dynamic load rating, radial
C <sub>0r</sub>	45.600 N	Basic static load rating, radial
G <sub>r</sub>	0 - 0,035	Radial Clearance
≈m	0,42 kg	Weight



## Dimensions

$d_K$	34,925 mm	Ball diameter
$d_1$	24,3 mm	Outer flange diameter inner ring
$d_2$	50 mm	Outer eye diameter
$d_3$	M20x1,5	Thread size
$d_4$	27,5 mm	Shank diameter
$h_1$	77 mm	Shank Length Internal thread head
$C_1$	18 mm	Width of the rod end
$\alpha$	14 °	Tilt angle
$l_3$	33 mm	Thread length Internal thread
$l_4$	102 mm	Total length internal thread head
$l_5$	10 mm	Length rod end shank
$l_7$	26 mm	Distance drilling with/shaft start
$d_5$	35 mm	Shank diameter, large
$r_{1smin}$	0,3 mm	Edge Spacing
$W$	30 mm	Width Across Flat
$d_{OT}$	0,021 mm	Bore diameter bearing, upper tolerance
$d_{UT}$	0 mm	Bore diameter bearing, lower tolerance
$d_T$	H7	Bore diameter bearing, tolerance
$B_{OT}$	0 mm	Width inner ring, upper tolerance
$B_{UT}$	-0,12 mm	Width inner ring, lower tolerance
$G_{rmax}$	0,035 mm	Radial clearance, maximum
$G_{rmin}$	0 mm	Radial clearance, minimum

## Temperature range

$T_{min}$	-60 °C	Operating temperature min.
$T_{max}$	250 °C	Operating temperature max.



### Characteristics

---



Radial load



Grease Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment