

**GIKR14-PB** [↗](#)

Rod end



Rod end with internal thread, right hand thread, requiring maintenance, DIN ISO 12240-4. dimension series K, type F, open design

Technical information



Your current product variant

Clampable	Not clampable
Maintenance	Maintenance required
Mounting	Internal thread
Lubrication nipple	DIN71412-AS6 (tapered grease nipple)
Slotted	No
Thread Pitch	Right-hand thread
Type of Sealing	Without

Main Dimensions & Performance Data

d	14 mm	Bore diameter bearing
D	28 mm	Outside diameter bearing
B	19 mm	Width inner ring
C _r	17.100 N	Basic dynamic load rating, radial
C _{0r}	32.000 N	Basic static load rating, radial
G _r	0 - 0,035	Radial Clearance
≈m	0,18 kg	Weight



Dimensions

d_K	25,4 mm	Ball diameter
d_1	16,8 mm	Outer flange diameter inner ring
d_2	36 mm	Outer eye diameter
d_3	M14	Thread size
d_4	21 mm	Shank diameter
h_1	57 mm	Shank Length Internal thread head
C_1	13,5 mm	Width of the rod end
α	16 °	Tilt angle
l_3	25 mm	Thread length Internal thread
l_4	75 mm	Total length internal thread head
l_5	8 mm	Length rod end shank
l_7	18 mm	Distance drilling with/shaft start
d_5	26 mm	Shank diameter, large
r_{1smin}	0,3 mm	Edge Spacing
W	22 mm	Width Across Flat
d_{OT}	0,018 mm	Bore diameter bearing, upper tolerance
d_{UT}	0 mm	Bore diameter bearing, lower tolerance
d_T	H7	Bore diameter bearing, tolerance
B_{OT}	0 mm	Width inner ring, upper tolerance
B_{UT}	-0,12 mm	Width inner ring, lower tolerance
G_{rmax}	0,035 mm	Radial clearance, maximum
G_{rmin}	0 mm	Radial clearance, minimum

Temperature range

T_{min}	-60 °C	Operating temperature min.
T_{max}	250 °C	Operating temperature max.



Characteristics



Radial load



Grease Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment