

**GIKR8-PB**

## Rod end



Rod end with internal thread, right hand thread, requiring maintenance, DIN ISO 12240-4. dimension series K, type F, open design

## Technical information



## Your current product variant

Clampable	Not clampable
Maintenance	Maintenance required
Lubrication nipple	DIN71412-AS6 (tapered grease nipple)
Slotted	No
Thread Pitch	Right-hand thread
Sealing	Without
Mounting	Internal thread

## Main Dimensions &amp; Performance Data

d	8 mm	Bore diameter bearing
D	19 mm	Outside diameter bearing
B	12 mm	Width inner ring
C <sub>r</sub>	7.140 N	Basic dynamic load rating, radial
C <sub>0r</sub>	13.100 N	Basic static load rating, radial
G <sub>r</sub>	0 - 0,035	Radial Clearance
≈m	49,445 g	Weight



## Dimensions

$d_K$	15,875 mm	Ball diameter
$d_1$	10,3 mm	Outer flange diameter inner ring
$d_2$	24 mm	Outer eye diameter
$d_3$	M8	Thread size
$d_4$	12,5 mm	Shank diameter
$h_1$	36 mm	Shank Length Internal thread head
$C_1$	9 mm	Width of the rod end
$\alpha$	14 °	Tilt angle
$l_3$	16 mm	Thread length Internal thread
$l_4$	48 mm	Total length internal thread head
$l_5$	5 mm	Length rod end shank
$l_7$	13 mm	Distance drilling with/shaft start
$d_5$	16 mm	Shank diameter, large
$r_{1smin}$	0,3 mm	Edge Spacing
$W$	14 mm	Width Across Flat
$d_{OT}$	0,015 mm	Bore diameter bearing, upper tolerance
$d_{UT}$	0 mm	Bore diameter bearing, lower tolerance
$d_T$	H7	Bore diameter bearing, tolerance
$B_{OT}$	0 mm	Width inner ring, upper tolerance
$B_{UT}$	-0,12 mm	Width inner ring, lower tolerance
$G_{rmax}$	0,035 mm	Radial clearance, maximum
$G_{rmin}$	0 mm	Radial clearance, minimum

## Temperature range

$T_{min}$	-60 °C	Operating temperature min.
$T_{max}$	250 °C	Operating temperature max.



### Characteristics

---



Radial load



Grease Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment