

**GIL40-DO-2RS**

## Rod end



Rod end with internal thread, left hand thread, requiring maintenance, sliding contact surface: steel/steel, DIN ISO 12240-4, dimension series E, type F, sealed

## Technical information



## Your current product variant

Clampable	Not clampable	
Maintenance	Maintenance required	
Lubrication nipple	DIN71412-AS6 (tapered grease nipple)	
Slotted	No	
Thread Pitch	Left-hand thread	
Sealing	2RS	Lip seals on both sides
Radial internal clearance	CN (Group N)	Normal internal clearance
Mounting	Internal thread	

## Main Dimensions &amp; Performance Data

d	40 mm	Bore diameter bearing
D	62 mm	Outside diameter bearing
B	28 mm	Width inner ring
$C_r$	129.000 N	Basic dynamic load rating, radial
$C_{0r}$	194.000 N	Basic static load rating, radial
$G_r$	0,043 - 0,12	Radial Clearance
$\approx m$	2,069 kg	Weight



## Dimensions

$d_K$	53 mm	Ball diameter
$d_1$	45 mm	Outer flange diameter inner ring
$d_2$	92 mm	Outer eye diameter
$d_3$	M39x3	Thread size
$d_4$	52 mm	Shank diameter
$h_1$	142 mm	Shank Length Internal thread head
$C_1$	23 mm	Width of the rod end
$\alpha$	7 °	Tilt angle
$l_3$	65 mm	Thread length Internal thread
$l_4$	188 mm	Total length internal thread head
$l_5$	18 mm	Length rod end shank
$l_7$	48 mm	Distance drilling with/shaft start
$d_5$	65 mm	Shank diameter, large
$r_{1smin}$	0,6 mm	Edge Spacing
$W$	55 mm	Width Across Flat
$d_{OT}$	0 mm	Bore diameter bearing, upper tolerance
$d_{UT}$	-0,012 mm	Bore diameter bearing, lower tolerance
$B_{OT}$	0 mm	Width inner ring, upper tolerance
$B_{UT}$	-0,12 mm	Width inner ring, lower tolerance
$G_{rmax}$	0,12 mm	Radial clearance, maximum
$G_{rmin}$	0,043 mm	Radial clearance, minimum

## Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	130 °C	Operating temperature max.



### Characteristics

---



Radial load



Grease Lubrication



Sealed on both sides



Static angular error and misalignment



Dynamic angular error and misalignment