

**GIR12-DO**

## Rod end



Rod end with internal thread, right hand thread, requiring maintenance, sliding contact surface: steel/steel, DIN ISO 12240-4, dimension series E, type F, open design

## Technical information

**Your current product variant**

Clampable	Not clampable
Maintenance	Maintenance required
Lubrication nipple	Cannot be relubricated
Slotted	No
Thread Pitch	Right-hand thread
Sealing	Without
Mounting	Internal thread
Radial internal clearance	CN (Group N)      Normal internal clearance

**Main Dimensions & Performance Data**

d	12 mm	Bore diameter bearing
D	22 mm	Outside diameter bearing
B	10 mm	Width inner ring
$C_r$	13.900 N	Basic dynamic load rating, radial
$C_{0r}$	30.400 N	Basic static load rating, radial
$G_r$	0,023 - 0,068	Radial Clearance
$m$	103,759 g	Weight



## Dimensions

d <sub>K</sub>	18 mm	Ball diameter
d <sub>1</sub>	14,9 mm	Outer flange diameter inner ring
d <sub>2</sub>	34 mm	Outer eye diameter
d <sub>3</sub>	M12	Thread size
d <sub>4</sub>	17,5 mm	Shank diameter
h <sub>1</sub>	50 mm	Shank Length Internal thread head
C <sub>1</sub>	8 mm	Width of the rod end
α	11 °	Tilt angle
l <sub>3</sub>	23 mm	Thread length Internal thread
l <sub>4</sub>	67 mm	Total length internal thread head
l <sub>5</sub>	6,5 mm	Length rod end shank
l <sub>7</sub>	18 mm	Distance drilling with/shaft start
d <sub>5</sub>	22 mm	Shank diameter, large
r <sub>1smin</sub>	0,3 mm	Edge Spacing
W	19 mm	Width Across Flat
d <sub>OT</sub>	0 mm	Bore diameter bearing, upper tolerance
d <sub>UT</sub>	-0,008 mm	Bore diameter bearing, lower tolerance
B <sub>OT</sub>	0 mm	Width inner ring, upper tolerance
B <sub>UT</sub>	-0,12 mm	Width inner ring, lower tolerance
G <sub>rmax</sub>	0,068 mm	Radial clearance, maximum
G <sub>rmin</sub>	0,023 mm	Radial clearance, minimum

## Temperature range

T <sub>min</sub>	-60 °C	Operating temperature min.
T <sub>max</sub>	200 °C	Operating temperature max.



### Characteristics

---



Radial load



Grease Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment