

**GIR17-DO**

## Rod end



Rod end with internal thread, right hand thread, requiring maintenance, sliding contact surface: steel/steel, DIN ISO 12240-4, dimension series E, type F, open design

## Technical information



## Your current product variant

Clampable	Not clampable	
Maintenance	Maintenance required	
Mounting	Internal thread	
Lubrication nipple	Lubrication hole	
Slotted	No	
Thread Pitch	Right-hand thread	
Type of Sealing	Without	
Radial internal clearance	CN (Group N)	Normal internal clearance

## Main Dimensions &amp; Performance Data

d	17 mm	Bore diameter bearing
D	30 mm	Outside diameter bearing
B	14 mm	Width inner ring
C <sub>r</sub>	27.600 N	Basic dynamic load rating, radial
C <sub>0r</sub>	56.500 N	Basic static load rating, radial
G <sub>r</sub>	0,03 - 0,082	Radial Clearance
≈m	0,238 kg	Weight



## Dimensions

d <sub>K</sub>	25 mm	Ball diameter
d <sub>1</sub>	20,7 mm	Outer flange diameter inner ring
d <sub>2</sub>	46 mm	Outer eye diameter
d <sub>3</sub>	M16	Thread size
d <sub>4</sub>	24 mm	Shank diameter
h <sub>1</sub>	67 mm	Shank Length Internal thread head
C <sub>1</sub>	11 mm	Width of the rod end
α	10 °	Tilt angle
l <sub>3</sub>	34 mm	Thread length Internal thread
l <sub>4</sub>	90 mm	Total length internal thread head
l <sub>5</sub>	10 mm	Length rod end shank
l <sub>7</sub>	23 mm	Distance drilling with/shaft start
d <sub>5</sub>	30 mm	Shank diameter, large
r <sub>1smin</sub>	0,3 mm	Edge Spacing
W	27 mm	Width Across Flat
d <sub>OT</sub>	0 mm	Bore diameter bearing, upper tolerance
d <sub>UT</sub>	-0,008 mm	Bore diameter bearing, lower tolerance
B <sub>OT</sub>	0 mm	Width inner ring, upper tolerance
B <sub>UT</sub>	-0,12 mm	Width inner ring, lower tolerance
G <sub>rmax</sub>	0,082 mm	Radial clearance, maximum
G <sub>rmin</sub>	0,03 mm	Radial clearance, minimum

## Temperature range

T <sub>min</sub>	-60 °C	Operating temperature min.
T <sub>max</sub>	200 °C	Operating temperature max.



### Characteristics

---



Radial load



Grease Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment