


**GIR25-DO**

## Rod end



Rod end with internal thread, right hand thread, requiring maintenance, sliding contact surface: steel/steel, DIN ISO 12240-4, dimension series E, type F, open design

## Technical information

**Your current product variant**

Clampable	Not clampable
Maintenance	Maintenance required
Lubrication nipple	DIN71412-AS6 (tapered grease nipple)
Slotted	No
Thread Pitch	Right-hand thread
Sealing	Without
Mounting	Internal thread
Radial internal clearance	CN (Group N)      Normal internal clearance

**Main Dimensions & Performance Data**

d	25 mm	Bore diameter bearing
D	42 mm	Outside diameter bearing
B	20 mm	Width inner ring
$C_r$	62.800 N	Basic dynamic load rating, radial
$C_{0r}$	88.300 N	Basic static load rating, radial
$G_r$	0,037 - 0,1	Radial Clearance
$\approx m$	0,636 kg	Weight



## Dimensions

$d_K$	35,5 mm	Ball diameter
$d_1$	29,3 mm	Outer flange diameter inner ring
$d_2$	64 mm	Outer eye diameter
$d_3$	M24x2	Thread size
$d_4$	33,5 mm	Shank diameter
$h_1$	94 mm	Shank Length Internal thread head
$C_1$	17 mm	Width of the rod end
$\alpha$	7 °	Tilt angle
$l_3$	48 mm	Thread length Internal thread
$l_4$	126 mm	Total length internal thread head
$l_5$	12 mm	Length rod end shank
$l_7$	32 mm	Distance drilling with/shaft start
$d_5$	42 mm	Shank diameter, large
$r_{1smin}$	0,6 mm	Edge Spacing
$W$	36 mm	Width Across Flat
$d_{OT}$	0 mm	Bore diameter bearing, upper tolerance
$d_{UT}$	-0,01 mm	Bore diameter bearing, lower tolerance
$B_{OT}$	0 mm	Width inner ring, upper tolerance
$B_{UT}$	-0,12 mm	Width inner ring, lower tolerance
$G_{rmax}$	0,1 mm	Radial clearance, maximum
$G_{rmin}$	0,037 mm	Radial clearance, minimum

## Temperature range

$T_{min}$	-60 °C	Operating temperature min.
$T_{max}$	200 °C	Operating temperature max.



### Characteristics

---



Radial load



Grease Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment