

**GIR60-DO-2RS**

Rod end



Rod end with internal thread, right hand thread, requiring maintenance, sliding contact surface: steel/steel, DIN ISO 12240-4, dimension series E, type F, sealed

Technical information



Your current product variant

Clampable	Not clampable	
Maintenance	Maintenance required	
Mounting	Internal thread	
Lubrication nipple	DIN71412-AS6 (tapered grease nipple)	
Slotted	No	
Thread Pitch	Right-hand thread	
Type of Sealing	2RS	Lip seals on both sides
Radial internal clearance	CN (Group N)	Normal internal clearance

Main Dimensions & Performance Data

d	60 mm	Bore diameter bearing
D	90 mm	Outside diameter bearing
B	44 mm	Width inner ring
C _r	318.000 N	Basic dynamic load rating, radial
C _{0r}	485.000 N	Basic static load rating, radial
G _r	0,043 - 0,12	Radial Clearance
≈m	5,6 kg	Weight



Dimensions

d_K	80 mm	Ball diameter
d_1	66,8 mm	Outer flange diameter inner ring
d_2	135 mm	Outer eye diameter
d_3	M52x3	Thread size
d_4	70 mm	Shank diameter
h_1	175 mm	Shank Length Internal thread head
C_1	38 mm	Width of the rod end
α	6 °	Tilt angle
l_3	70 mm	Thread length Internal thread
l_4	242,5 mm	Total length internal thread head
l_5	20 mm	Length rod end shank
l_7	75 mm	Distance drilling with/shaft start
d_5	88 mm	Shank diameter, large
r_{1smin}	1 mm	Edge Spacing
W	75 mm	Width Across Flat
d_{OT}	0 mm	Bore diameter bearing, upper tolerance
d_{UT}	-0,015 mm	Bore diameter bearing, lower tolerance
B_{OT}	0 mm	Width inner ring, upper tolerance
B_{UT}	-0,15 mm	Width inner ring, lower tolerance
G_{rmax}	0,12 mm	Radial clearance, maximum
G_{rmin}	0,043 mm	Radial clearance, minimum

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	130 °C	Operating temperature max.



Characteristics



Radial load



Grease Lubrication



Sealed on both sides



Static angular error and misalignment



Dynamic angular error and misalignment