


**GAKLB22-PC**

Rod end

Rod end with external thread, left hand thread, requiring maintenance, sliding contact surface: steel/bronze, DIN ISO 12240-4, dimension series K, type M, open design

Technical information

**Your current product variant**

Clampable	Not clampable
Maintenance	Maintenance required
Lubrication nipple	DIN3405 (funnel-type grease nipple)
Slotted	No
Thread Pitch	Left-hand thread
Sealing	Without
Radial internal clearance	CN (Group N) Normal internal clearance
Mounting	External thread

Main Dimensions & Performance Data

C_r	35.800 N	Basic dynamic load rating, radial
C_{0r}	48.800 N	Basic static load rating, radial
d	22 mm	Bore diameter bearing
D	42 mm	Outside diameter bearing
l_2	111,5 mm	Total length external thread head
B	28 mm	Width inner ring
d_2	55 mm	Outer eye diameter
$\approx m$	435 g	Weight



Mounting dimensions

d ₁	25,8 mm	Outer flange diameter inner ring
r _{1smin}	0,3 mm	Edge Spacing

Dimensions








d _K	38,1 mm	Ball diameter
d ₃	M22X1,5-LH	Thread size
h	84 mm	Shank Length External thread rod
C ₁	20 mm	Width of the rod end
α	15 °	Tilt angle
l ₁	48 mm	Shank Length External thread head
l ₇	26 mm	Distance drilling with/shaft start
d _{OT}	0,021 mm	Bore diameter bearing, upper tolerance
d _{UT}	0 mm	Bore diameter bearing, lower tolerance
d _T	H7	Bore diameter bearing, tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
B _{UT}	-0,12 mm	Width inner ring, lower tolerance
G _r	0,01 - 0,055	Radial Clearance
G _{rmax}	0,055 mm	Radial clearance, maximum
G _{rmin}	0,01 mm	Radial clearance, minimum

Temperature range

T _{min}	-50 °C	Operating temperature min.
T _{max}	250 °C	Operating temperature max.



Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment