

**GIKRB18-PD**

## Rod end

Rod end GIKR..-PW, internal threads,  
maintenance-free

## Technical information

**Your current product variant**

Clampable	Not clampable
Maintenance	Maintenance free
Mounting	Internal thread
Lubrication nipple	Cannot be relubricated
Slotted	No
Thread Pitch	Right-hand thread
Sealing	Without

**Main Dimensions & Performance Data**

$C_r$	47.500 N	Basic dynamic load rating, radial
$C_{0r}$	23.000 N	Basic static load rating, radial
d	18 mm	Bore diameter bearing
$d_2$	47 mm	Outer eye diameter
$l_4$	94,5 mm	Total length internal thread head
$\approx m$	0,311 kg	Weight



## Dimensions

C <sub>1</sub>	16,5 mm	Width of the rod end
D	35 mm	Outside diameter bearing
B	23 mm	Width inner ring
d <sub>K</sub>	31,7 mm	Ball diameter
d <sub>3</sub>	M18x1,5	Thread size
d <sub>4</sub>	25 mm	Shank diameter
d <sub>5</sub>	31 mm	Shank diameter, large
h <sub>1</sub>	71 mm	Shank Length Internal thread head
α	15 °	Tilt angle
l <sub>3</sub>	27 mm	Thread length Internal thread
l <sub>5</sub>	10 mm	Length rod end shank
l <sub>7</sub>	23 mm	Distance drilling with/shaft start
W	27 mm	Width Across Flat
d <sub>UT</sub>	0 mm	Bore diameter bearing, lower tolerance
d <sub>T</sub>	H7	Bore diameter bearing, tolerance
d <sub>OT</sub>	0,018 mm	Bore diameter bearing, upper tolerance
B <sub>UT</sub>	0 mm	Width inner ring, lower tolerance
B <sub>OT</sub>	-0,12 mm	Width inner ring, upper tolerance
G <sub>r</sub>	0,005-0,045	Radial Clearance
G <sub>rmin</sub>	0,005 mm	Radial clearance, minimum
G <sub>rmax</sub>	0,045 mm	Radial clearance, maximum

## Mounting dimensions



r <sub>1smin</sub>	0,3 mm	Edge Spacing
d <sub>1</sub>	21,9 mm	Outer flange diameter inner ring



### Temperature range

$T_{\min}$	-50 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment