


**GIHNRK40-LO**

## Rod end



Hydraulic rod end, with thread clamping device, right hand thread, requiring maintenance, sliding contact surface: steel/steel, DIN 24338 ISO 6982, open design

## Technical information

**Your current product variant**

Clampable	Clampable
Maintenance	Maintenance required
Mounting	Internal thread
Lubrication nipple	DIN71412-AS6 (tapered grease nipple)
Slotted	Slotted, both sides
Thread Pitch	Right-hand thread
Sealing	Without

**Main Dimensions & Performance Data**

$C_r$	129.000 N	Basic dynamic load rating, radial
$C_{0r}$	176.000 N	Basic static load rating, radial
$d$	40 mm	Bore diameter bearing
$d_2$	89 mm	Outer eye diameter
$l_4$	141,5 mm	Total length internal thread head
$D$	62 mm	Outside diameter bearing
$B$	40 mm	Width inner ring
$\approx m$	1,912 kg	Weight



## Dimensions

$\alpha$	4 °	Tilt angle
C <sub>1</sub>	32 mm	Width of the rod end
C <sub>2</sub>	26 mm	Width
d <sub>K</sub>	53 mm	Ball diameter
d <sub>3</sub>	M33x2	Thread size
d <sub>4</sub>	47 mm	Shank diameter
d <sub>5</sub>	80 mm	Shank diameter, large
d <sub>7</sub>	M10x25	Diameter screw clamp
h <sub>1</sub>	97 mm	Shank Length Internal thread head
l <sub>3</sub>	46 mm	Thread length Internal thread
l <sub>7</sub>	41 mm	Distance drilling with/shaft start
d <sub>UT</sub>	0 mm	Bore diameter bearing, lower tolerance
d <sub>T</sub>	H7	Bore diameter bearing, tolerance
d <sub>OT</sub>	0,025 mm	Bore diameter bearing, upper tolerance
B <sub>UT</sub>	-0,25 mm	Width inner ring, lower tolerance
B <sub>OT</sub>	0 mm	Width inner ring, upper tolerance
M <sub>A</sub>	64 Nm	Tightening torque
F <sub>Z</sub>	80.000 N	Cylinder Force
G <sub>r</sub>	0,043 - 0,12	Radial Clearance
G <sub>rmin</sub>	0,043 mm	Radial clearance, minimum
G <sub>rmax</sub>	0,12 mm	Radial clearance, maximum

## Mounting dimensions






r <sub>1smin</sub>	0,6 mm	Edge Spacing
d <sub>1</sub>	46 mm	Outer flange diameter inner ring



### Temperature range

$T_{\min}$	-60 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Grease Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment