


**GIHRK60-DO**

## Rod end



Hydraulic rod end, with thread clamping device, right hand thread, requiring maintenance, sliding contact surface: steel/steel, open design

## Technical information

**Your current product variant**

|                           |   |
|---------------------------|---|
| Clampable                 | Clampable                                   |
| Maintenance               | Maintenance required                        |
| Lubrication nipple        | DIN71412-AS6 (tapered grease nipple)        |
| Slotted                   | Slotted, both sides                         |
| Thread Pitch              | Right-hand thread                           |
| Sealing                   | Without                                     |
| Mounting                  | Internal thread clampable                   |
| Radial internal clearance | CN (Group N)      Normal internal clearance |

**Main Dimensions & Performance Data**

|             |           |                                   |
|-------------|-----------|-----------------------------------|
| $C_r$       | 318.000 N | Basic dynamic load rating, radial |
| $C_{0r}$    | 327.000 N | Basic static load rating, radial  |
| $d$         | 60 mm     | Bore diameter bearing             |
| $d_2$       | 130 mm    | Outer eye diameter                |
| $l_4$       | 200 mm    | Total length internal thread head |
| $D$         | 90 mm     | Outside diameter bearing          |
| $B$         | 44 mm     | Width inner ring                  |
| $\approx m$ | 5,621 kg  | Weight                            |



## Dimensions

|                   |              |  |
|-------------------|--------------|--|
| $\alpha$          | 6 °          | Tilt angle                             |
| C <sub>1</sub>    | 50 mm        | Width of the rod end                   |
| d <sub>K</sub>    | 80 mm        | Ball diameter                          |
| d <sub>3</sub>    | M58x1,5      | Thread size                            |
| d <sub>4</sub>    | 75 mm        | Shank diameter                         |
| d <sub>5</sub>    | 90 mm        | Shank diameter, large                  |
| d <sub>7</sub>    | M10x45       | Diameter screw clamp                   |
| h <sub>1</sub>    | 130 mm       | Shank Length Internal thread head      |
| l <sub>3</sub>    | 59 mm        | Thread length Internal thread          |
| l <sub>7</sub>    | 65 mm        | Distance drilling with/shaft start     |
| d <sub>UT</sub>   | -0,015 mm    | Bore diameter bearing, lower tolerance |
| d <sub>OT</sub>   | 0 mm         | Bore diameter bearing, upper tolerance |
| B <sub>UT</sub>   | -0,15 mm     | Width inner ring, lower tolerance      |
| B <sub>OT</sub>   | 0 mm         | Width inner ring, upper tolerance      |
| M <sub>A</sub>    | 46 Nm        | Tightening torque                      |
| G <sub>r</sub>    | 0,043 - 0,12 | Radial Clearance                       |
| G <sub>rmin</sub> | 0,043 mm     | Radial clearance, minimum              |
| G <sub>rmax</sub> | 0,12 mm      | Radial clearance, maximum              |

## Mounting dimensions

|                    |         |                                  |
|--------------------|---------|----------------------------------|
| r <sub>1smin</sub> | 1 mm    | Edge Spacing                     |
| d <sub>1</sub>     | 66,8 mm | Outer flange diameter inner ring |

## Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -60 °C | Operating temperature min. |
| T <sub>max</sub> | 200 °C | Operating temperature max. |



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment