

**GE15-UK** [↗](#)

Spherical plain bearing

Radial spherical plain bearing, maintenance-free, sliding layer: PTFE composite, inner ring curved surface with hard chromium coating, DIN ISO 12240-1, dimension series E, open design

Technical information

**Your current product variant**

Maintenance	Maintenance free
Type of Sealing	Without Without
Bore lining	Without
Coating	Without
Fabric	PTFE-composite Composite Material based on a steel backing, sintered bronze layer, with inserted plastic material.
Material	Steel

Main Dimensions & Performance Data

d	15 mm	Bore diameter bearing
C_r	17.800 N	Basic dynamic load rating, radial
D	26 mm	Outside diameter bearing
B	12 mm	Width inner ring
C	9 mm	Width Outer ring
C_{0r}	44.600 N	Basic static load rating, radial
m	26,15 g	Weight

Mounting dimensions

$r_{1\text{min}}$	0,3 mm	Edge Spacing
$r_{2\text{min}}$	0,3 mm	Edge Spacing
D_{amin}	21 mm	Housing Connection Diameter
d_{amax}	18,4 mm	Connection measurement, inner ring










Dimensions

d_K	22 mm	Ball diameter
α	8 °	Tilt angle
D_{OT}	0 mm	Outside diameter, upper tolerance
D_{UT}	-0,009 mm	Outside diameter, lower tolerance
B_{OT}	0 mm	Width inner ring, upper tolerance
d_{UT}	-0,008 mm	Bore diameter bearing, lower tolerance
B_{UT}	-0,12 mm	Width inner ring, lower tolerance
d_{OT}	0 mm	Bore diameter bearing, upper tolerance
C_{OT}	0 mm	Width outer ring, upper tolerance
C_{UT}	-0,24 mm	Width outer ring, lower tolerance
G_r	0 - 0,04	Radial Clearance
G_{rmax}	0,04 mm	Radial clearance, maximum
G_{rmin}	0 mm	Radial clearance, minimum

Temperature range

T_{min}	-50 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Not sealed
	Static angular error and misalignment
	Dynamic angular error and misalignment