

**GE260-UK-2RS** [↗](#)

## Spherical plain bearing

Radial spherical plain bearing, maintenance-free, sliding layer: ELGOGLIDE, DIN ISO 12240-1, Tolerances of the outside diameter and bore not according to DIN ISO 12240-1, dimension series E, sealed

## Technical information



## Your current product variant

Maintenance	Maintenance free
Sealing	2RS Lip seal on both sides
Bore lining	Without
Coating	Without
Fabric	ELGOGLIDE
Material	Steel

## Main Dimensions &amp; Performance Data

d	260 mm	Bore diameter bearing
C <sub>r</sub>	8.580.000 N	Basic dynamic load rating, radial
D	370 mm	Outside diameter bearing
B	150 mm	Width inner ring
C	110 mm	Width Outer ring
C <sub>0r</sub>	14.300.000 N	Basic static load rating, radial
≈m	50,4 kg	Weight

## Mounting dimensions

r <sub>1smin</sub>	1,1 mm	Edge Spacing
r <sub>2smin</sub>	1,1 mm	Edge Spacing
D <sub>amin</sub>	319 mm	Housing Connection Diameter
d <sub>amax</sub>	288,3 mm	Connection measurement, inner ring











## Dimensions

$d_K$	325 mm	Ball diameter
$\alpha$	7 °	Tilt angle
$D_{OT}$	0 mm	Outside diameter, upper tolerance
$D_{UT}$	-0,04 mm	Outside diameter, lower tolerance
$B_{OT}$	0 mm	Width inner ring, upper tolerance
$d_{UT}$	-0,035 mm	Bore diameter bearing, lower tolerance
$B_{UT}$	-0,35 mm	Width inner ring, lower tolerance
$d_{OT}$	0 mm	Bore diameter bearing, upper tolerance
$C_{OT}$	0 mm	Width outer ring, upper tolerance
$C_{UT}$	-0,8 mm	Width outer ring, lower tolerance
$G_r$	0 - 0,125 mm	Radial Clearance
$G_{rmax}$	0,125 mm	Radial clearance, maximum
$G_{rmin}$	0 mm	Radial clearance, minimum

## Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	130 °C	Operating temperature max.

## Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Sealed on both sides
	Large bearing
	Static angular error and misalignment
	Dynamic angular error and misalignment