

**GE100-AW**

Spherical plain bearing

Axial spherical plain bearing, maintenance-free, DIN ISO 12240-3, shaft location washer curved surface with hard chromium coating, open design

Technical information



Your current product variant

Maintenance	Maintenance free
Coating	Without
Material sliding Layer	ELGOGLIDE

Main Dimensions & Performance Data

d	100 mm	Bore diameter bearing
D	210 mm	Outside diameter bearing
T	59 mm	Height
B	50 mm	Width inner ring
C _a	3.610.000 N	Basic dynamic load rating, axial
C _{0a}	6.020.000 N	Basic static load rating, axial
≈m	10,76 kg	Weight

Mounting dimensions

r _{1smin}	1 mm	Edge Spacing
r _{2smin}	0,3 mm	Edge Spacing
d _{a max}	155 mm	Connection measure Inner ring
D _{a min}	141 mm	Housing Connection Diameter



Dimensions

d_K	220 mm	Ball diameter
d_2	195,5 mm	Outer eye diameter
d_3	155 mm	Front surface diameter of shaft washer
D_1	133 mm	Bore diameter of housing washer
C	42 mm	Width Outer ring
s	45 mm	Plane Surface Spacing
α	7 °	Tilt angle
d_{OT}	0 mm	Bore diameter bearing, upper tolerance
d_{UT}	-0,02 mm	Bore diameter bearing, lower tolerance
D_{OT}	0 mm	Outside diameter, upper tolerance
D_{UT}	-0,03 mm	Outside diameter, lower tolerance
T_{OT}	0 mm	Height, upper tolerance
B_{OT}	0 mm	Width inner ring, upper tolerance
T_{UT}	-0,4 mm	Height, lower tolerance
B_{UT}	-0,4 mm	Width inner ring, lower tolerance
C_{OT}	0 mm	Width outer ring, upper tolerance
C_{UT}	-0,4 mm	Width outer ring, lower tolerance

Temperature range

T_{min}	-50 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.



Characteristics



Radial load



Axial load in one direction



Lifetime lubrication, freedom from maintenance



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment