

**GE120-AW**

## Spherical plain bearing

Axial spherical plain bearing, maintenance-free, DIN ISO 12240-3, shaft location washer curved surface with hard chromium coating, open design

## Technical information

**Your current product variant**

Maintenance	Maintenance free
Coating	Without
Material sliding Layer	ELGOGLIDE

**Main Dimensions & Performance Data**

d	120 mm	Bore diameter bearing
D	230 mm	Outside diameter bearing
T	64 mm	Height
B	52 mm	Width inner ring
C <sub>a</sub>	3.740.000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	6.230.000 N	Basic static load rating, axial
≈m	13,2 kg	Weight

**Mounting dimensions**

r <sub>1smin</sub>	1 mm	Edge Spacing
r <sub>2smin</sub>	0,3 mm	Edge Spacing
d <sub>a max</sub>	170 mm	Connection measure Inner ring
D <sub>a min</sub>	162 mm	Housing Connection Diameter



## Dimensions

$d_K$	245 mm	Ball diameter
$d_2$	214 mm	Outer eye diameter
$d_3$	170 mm	Front surface diameter of shaft washer
$D_1$	154 mm	Bore diameter of housing washer
$C$	45 mm	Width Outer ring
$s$	52,5 mm	Plane Surface Spacing
$\alpha$	6,5 °	Tilt angle
$d_{OT}$	0 mm	Bore diameter bearing, upper tolerance
$d_{UT}$	-0,02 mm	Bore diameter bearing, lower tolerance
$D_{OT}$	0 mm	Outside diameter, upper tolerance
$D_{UT}$	-0,03 mm	Outside diameter, lower tolerance
$T_{OT}$	0 mm	Height, upper tolerance
$B_{OT}$	0 mm	Width inner ring, upper tolerance
$T_{UT}$	-0,5 mm	Height, lower tolerance
$B_{UT}$	-0,4 mm	Width inner ring, lower tolerance
$C_{OT}$	0 mm	Width outer ring, upper tolerance
$C_{UT}$	-0,4 mm	Width outer ring, lower tolerance

## Temperature range

$T_{min}$	-50 °C	Operating temperature min.
$T_{max}$	150 °C	Operating temperature max.



### Characteristics

---



Radial load



Axial load in one direction



Lifetime lubrication, freedom from maintenance



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment