




**GE240-AW-XL**

Spherical plain bearing

Spherical plain bearing GE...-AW-A-XL, axial/
oblique, maintenance-free

X-life

Technical information



Your current product variant

Maintenance	Maintenance free
Coating	Without

Main Dimensions & Performance Data

d	240 mm	Bore diameter bearing
D	400 mm	Outside diameter bearing
T	103 mm	Height
B	87 mm	Width inner ring
C _a	10.300.000 N	Basic dynamic load rating, axial
C _{0a}	17.200.000 N	Basic static load rating, axial
≈m	57,6 kg	Weight

Mounting dimensions

r _{1smin}	1,5 mm	Edge Spacing
r _{2smin}	0,6 mm	Edge Spacing
d _{a max}	314 mm	Connection measure Inner ring
D _{a min}	309 mm	Housing Connection Diameter



Dimensions

d_K	420 mm	Ball diameter
d_2	382 mm	Outer eye diameter
d_3	314 mm	Front surface diameter of shaft washer
D_1	294 mm	Bore diameter of housing washer
C	73 mm	Width Outer ring
s	77,5 mm	Plane Surface Spacing
α	6 °	Tilt angle
d_{OT}	0 mm	Bore diameter bearing, upper tolerance
d_{UT}	-0,03 mm	Bore diameter bearing, lower tolerance
D_{OT}	0 mm	Outside diameter, upper tolerance
D_{UT}	-0,04 mm	Outside diameter, lower tolerance
T_{OT}	0 mm	Height, upper tolerance
B_{OT}	0 mm	Width inner ring, upper tolerance
T_{UT}	-0,6 mm	Height, lower tolerance
B_{UT}	-0,6 mm	Width inner ring, lower tolerance
C_{OT}	0 mm	Width outer ring, upper tolerance
C_{UT}	-0,6 mm	Width outer ring, lower tolerance

Temperature range

T_{min}	-50 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.



Characteristics



Radial load



Axial load in one direction



Lifetime lubrication, freedom from maintenance



Not sealed



Large bearing



Static angular error and misalignment



Dynamic angular error and misalignment