

**GE35-HO-2RS**

Spherical plain bearing



High performance Radial spherical plain bearing, requiring maintenance, sliding contact surface: steel/steel, cylindrical extensions on inner ring, sealed High-performance: For highest load rating and lifetime demands

Technical information



Your current product variant

| | | |
|---------------------------|----------------------|--|
| Maintenance | Maintenance required | |
| Material | Steel | |
| Type of Seal | 2RS | Lip seals on both sides |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Coating | Durotect M | Inner- and outer ring coated with Durotect M (Manganese Phosphate) |

Main Dimensions & Performance Data

| | | |
|-------------|-----------|-----------------------------------|
| d | 35 mm | Bore diameter bearing |
| D | 55 mm | Outside diameter bearing |
| B | 35 mm | Width inner ring |
| C_r | 104.000 N | Basic dynamic load rating, radial |
| C_{0r} | 400.000 N | Basic static load rating, radial |
| $\approx m$ | 0,237 kg | Weight |

Mounting dimensions

| | | |
|-------------------|---------|-------------------------------|
| $r_{1\text{min}}$ | 0,3 mm | Edge Spacing |
| $r_{2\text{min}}$ | 1 mm | Edge Spacing |
| $d_{a\text{max}}$ | 40 mm | Connection measure Inner ring |
| $D_{a\text{min}}$ | 44,5 mm | Housing Connection Diameter |



Dimensions

| | | |
|------------|------------|--|
| C | 20 mm | Width Outer ring |
| d_K | 47 mm | Ball diameter |
| α | 3 ° | Tilt angle |
| d_{OT} | 0 mm | Bore diameter bearing, upper tolerance |
| d_{UT} | -0,012 mm | Bore diameter bearing, lower tolerance |
| D_{OT} | 0 mm | Outside diameter, upper tolerance |
| D_{UT} | -0,013 mm | Outside diameter, lower tolerance |
| B_{OT} | 0,3 mm | Width inner ring, upper tolerance |
| B_{UT} | -0,3 mm | Width inner ring, lower tolerance |
| C_{OT} | 0 mm | Width outer ring, upper tolerance |
| C_{UT} | -0,3 mm | Width outer ring, lower tolerance |
| G_r | 0,05 - 0,1 | Radial Clearance |
| G_{rmax} | 0,1 mm | Radial clearance, maximum |
| G_{rmin} | 0,05 mm | Radial clearance, minimum |

Temperature range

| | | |
|-----------|--------|----------------------------|
| T_{min} | -30 °C | Operating temperature min. |
| T_{max} | 130 °C | Operating temperature max. |

Characteristics

| | |
|---|--|
|  | Radial load |
|  | Axial load in one direction |
|  | Axial load in two directions |
|  | Grease Lubrication |
|  | Sealed on both sides |
|  | Static angular error and misalignment |
|  | Dynamic angular error and misalignment |