

**GE160-LO**

## Spherical plain bearing

High performance Radial spherical plain bearing, requiring maintenance, sliding contact surface: steel/steel, DIN ISO 12240-1, dimension series W, cylindrical extensions on inner ring, open design High-performance: For highest load rating and lifetime demands

## Technical information



## Your current product variant

|                           |                      |  |
|---------------------------|----------------------|--|
| Maintenance               | Maintenance required |  |
| Material                  | Steel                |  |
| Sealing                   | Without              |  |
| Radial internal clearance | CN (Group N)         | Normal internal clearance  |
| Coating                   | Durotect M           | Inner- and outer ring coated with Durotect M (Manganese Phosphate) |

## Main Dimensions &amp; Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 160 mm      | Bore diameter bearing             |
| D               | 230 mm      | Outside diameter bearing          |
| B               | 160 mm      | Width inner ring                  |
| C <sub>r</sub>  | 1.770.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 6.800.000 N | Basic static load rating, radial  |
| ≈m              | 16,2 kg     | Weight                            |

## Mounting dimensions

|                    |        |                               |
|--------------------|--------|-------------------------------|
| r <sub>1smin</sub> | 1 mm   | Edge Spacing                  |
| r <sub>2smin</sub> | 1 mm   | Edge Spacing                  |
| d <sub>a max</sub> | 177 mm | Connection measure Inner ring |
| D <sub>a min</sub> | 191 mm | Housing Connection Diameter   |



## Dimensions

|                   |             |  |
|-------------------|-------------|--|
| C                 | 80 mm       | Width Outer ring                       |
| d <sub>K</sub>    | 200 mm      | Ball diameter                          |
| α                 | 4 °         | Tilt angle                             |
| d <sub>OT</sub>   | 0,04 mm     | Bore diameter bearing, upper tolerance |
| d <sub>UT</sub>   | 0 mm        | Bore diameter bearing, lower tolerance |
| D <sub>OT</sub>   | 0 mm        | Outside diameter, upper tolerance      |
| D <sub>UT</sub>   | -0,03 mm    | Outside diameter, lower tolerance      |
| B <sub>OT</sub>   | 0 mm        | Width inner ring, upper tolerance      |
| B <sub>UT</sub>   | -0,4 mm     | Width inner ring, lower tolerance      |
| C <sub>OT</sub>   | 0 mm        | Width outer ring, upper tolerance      |
| C <sub>UT</sub>   | -0,6 mm     | Width outer ring, lower tolerance      |
| G <sub>r</sub>    | 0,1 - 0,192 | Radial Clearance                       |
| G <sub>rmax</sub> | 0,192 mm    | Radial clearance, maximum              |
| G <sub>rmin</sub> | 0,1 mm      | Radial clearance, minimum              |

## Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -60 °C | Operating temperature min. |
| T <sub>max</sub> | 200 °C | Operating temperature max. |

## Characteristics

|   |  |
|---|--|
|  | Radial load                            |
|  | Axial load in one direction            |
|  | Axial load in two directions           |
|  | Grease Lubrication                     |
|  | Not sealed                             |
|  | Static angular error and misalignment  |
|  | Dynamic angular error and misalignment |