


**GE100-AX**

## Spherical plain bearing



Axial spherical plain bearing, requiring maintenance, sliding contact surface: steel/steel

## Technical information

**Your current product variant**

Maintenance	Maintenance required
Coating	Durotect M Inner- and outer ring coated with Durotect M (Manganese Phosphate)

**Main Dimensions & Performance Data**

d	100 mm	Inner diameter bearing
D	210 mm	Outside diameter bearing
T	59 mm	Height
C <sub>a</sub>	1.570.000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	6.020.000 N	Basic static load rating, axial
≈m	10,76 kg	Weight

**Mounting dimensions**

r <sub>1smin</sub>	1 mm	Edge Spacing
r <sub>2smin</sub>	0,3 mm	Edge Spacing
d <sub>a max</sub>	155 mm	Connection measure Inner ring
D <sub>a min</sub>	141 mm	Housing Connection Diameter



## Dimensions

$d_K$	220 mm	Ball diameter
$d_3$	155	Front surface diameter of shaft washer
$D_1$	133 mm	Inner diameter of housing washer
$B$	50 mm	Width Inner ring
$C$	42 mm	Width Outer ring
$s$	45 mm	Plane Surface Spacing
$A$	15 mm	Distance lubrication Bore
$\alpha$	7 °	Tilt angle
$d_{OT}$	0 mm	Bore diameter bearing, upper tolerance
$d_{UT}$	-0,02 mm	Bore diameter bearing, lower tolerance
$D_{OT}$	0 mm	Outer diameter, upper tolerance
$D_{UT}$	-0,03 mm	Outside diameter, lower tolerance
$T_{OT}$	0 mm	Height, upper tolerance
$T_{UT}$	-0,4 mm	Height, lower tolerance
$C_{UT}$	0 mm	Width outer ring, upper tolerance
$C_{OT}$	-0,4 mm	Width outer ring, lower tolerance
$B_{OT}$	0 mm	Width inner ring, upper tolerance
$B_{UT}$	-0,4 mm	Width inner ring, lower tolerance
$d_2$	195,5 mm	Connection measure Inner ring

## Temperature range

$T_{min}$	-60 °C	Operating temperature min.
$T_{max}$	200 °C	Operating temperature max.



### Characteristics

---



Radial load



Axial load in one direction



Grease Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment