

**EGB0403-E40**

## Bush

Metal/polymer composite plain bush,  
maintenance-free, ISO 3547, with steel  
backing

## Technical information



## Your current product variant

Maintenance	Maintenance free	
Type of Sealing	Without	Not sealed
Material sliding Layer	E40	Maintenance-free sliding layer E40
Material back	Steel	

## Main Dimensions &amp; Performance Data

$D_i$	4 mm	Inner diameter
$D_o$	5,5 mm	Outer diameter
B	3 mm	Width
$C_r$	1.680 N	Basic dynamic load rating, radial
$C_{0r}$	3.000 N	Basic static load rating, radial
$\approx m$	200 mg	Weight



## Dimensions

$f$	20 °	Chamfer angle outside diameter
$f$	0,5 mm	Outer chamfer
$F_{i\ min}$	0,1 mm	Inner edge break, min.
$F_{i\ max}$	0,4 mm	Inner edge break, max.
$D_{i\ OT}$	0,048 mm	Inner diameter, upper tolerance
$D_{o\ OT}$	0,055 mm	Outside diameter, upper tolerance
$D_{i\ UT}$	0,008 mm	Inner diameter, lower tolerance
$D_{o\ UT}$	0,025 mm	Outside diameter, lower tolerance
$s_3$	0,75 mm	Wall thickness
$s_3\ OT$	0 mm	Wall thickness, upper tolerance
$s_3\ UT$	-0,02 mm	Wall thickness, lower tolerance
$B_{UT}$	-0,25 mm	Width, lower tolerance
$B_{OT}$	0,25 mm	Width, upper tolerance
$f_{OT}$	0,3 mm	Outer chamfer, upper tolerance
$f_{UT}$	-0,3 mm	Outer chamfer, lower tolerance
$F_i$	0,1 mm	Inner edge break

## Temperature range

$T_{min}$	-200 °C	Operating temperature min.
$T_{max}$	280 °C	Operating temperature max.

## Characteristics



Radial load



Lifetime lubrication, freedom from maintenance



Not sealed



Small design envelope