

**EGB1510-E50**

Bush

Metal/polymer composite plain bush, low-maintenance, ISO 3547, with steel backing



Technical information



Your current product variant

Maintenance	Low-maintenance	
Type of Sealing	Without	Not sealed
Material sliding Layer	E50	Low-maintenance sliding layer with lubrication pockets E50
Material back	Steel	

Main Dimensions & Performance Data

D_i	15 mm	Inner diameter
D_o	17 mm	Outer diameter
B	10 mm	Width
C_r	10.500 N	Basic dynamic load rating, radial
C_{0r}	21.000 N	Basic static load rating, radial
m	2,7 g	Weight



Dimensions

f	20 °	Chamfer angle outside diameter
d _L	3 mm	Diameter lubrication hole
f	0,6 mm	Outer chamfer
F _{i min}	0,1 mm	Inner edge break, min.
F _{i max}	0,6 mm	Inner edge break, max.
D _{i OT}	0,099 mm	Inner diameter, upper tolerance
D _{o OT}	0,065 mm	Outside diameter, upper tolerance
D _{i UT}	0,049 mm	Inner diameter, lower tolerance
D _{o UT}	0,03 mm	Outside diameter, lower tolerance
s ₃	1 mm	Wall thickness
s _{3 OT}	0,005 mm	Wall thickness, upper tolerance
s _{3 UT}	-0,02 mm	Wall thickness, lower tolerance
B _{UT}	-0,25 mm	Width, lower tolerance
B _{OT}	0,25 mm	Width, upper tolerance
f _{OT}	0,4 mm	Outer chamfer, upper tolerance
f _{UT}	-0,4 mm	Outer chamfer, lower tolerance
F _i	0,1 mm	Inner edge break

Temperature range

T _{min}	-40 °C	Operating temperature min.
T _{max}	110 °C	Operating temperature max.

Characteristics

	Radial load
	Grease Lubrication
	Not sealed
	Small design envelope