

**EGB0610-E40**

Bush

Metal/polymer composite plain bush,
maintenance-free, ISO 3547, with steel
backing

Technical information



Your current product variant

Maintenance	Maintenance free	
Sealing	Without	Not sealed
Material sliding Layer	E40	Maintenance-free sliding layer E40
Material back	Steel	

Main Dimensions & Performance Data

D_i	6 mm	Inner diameter
D_o	8 mm	Outer diameter
B	10 mm	Width
C_r	8.400 N	Basic dynamic load rating, radial
C_{0r}	15.000 N	Basic static load rating, radial
$\approx m$	1,5 g	Weight



Dimensions

f	20 °	Chamfer angle outside diameter
f	0,6 mm	Outer chamfer
$F_{i \min}$	0,1 mm	Inner edge break, min.
$F_{i \max}$	0,6 mm	Inner edge break, max.
$D_{i OT}$	0,048 mm	Inner diameter, upper tolerance
$D_{o OT}$	0,055 mm	Outside diameter, upper tolerance
$D_{i UT}$	-0,002 mm	Inner diameter, lower tolerance
$D_{o UT}$	0,025 mm	Outside diameter, lower tolerance
s_3	1 mm	Wall thickness
$s_3 OT$	0,005 mm	Wall thickness, upper tolerance
$s_3 UT$	-0,02 mm	Wall thickness, lower tolerance
B_{UT}	-0,25 mm	Width, lower tolerance
B_{OT}	0,25 mm	Width, upper tolerance
f_{OT}	0,4 mm	Outer chamfer, upper tolerance
f_{UT}	-0,4 mm	Outer chamfer, lower tolerance
F_i	0,1 mm	Inner edge break

Temperature range

T_{\min}	-200 °C	Operating temperature min.
T_{\max}	280 °C	Operating temperature max.

Characteristics



Radial load



Lifetime lubrication, freedom from maintenance



Not sealed



Small design envelope