



EGB2030-E40

Bush

Metal/polymer composite plain bush, maintenance-free, ISO 3547, with steel backing



Technical information



Your current product variant

| | | |
|------------------------|------------------|------------------------------------|
| Maintenance | Maintenance free | |
| Type of Sealing | Without | Not sealed |
| Material sliding Layer | E40 | Maintenance-free sliding layer E40 |
| Material back | Steel | |

Main Dimensions & Performance Data

| | | |
|-----------------|-----------|-----------------------------------|
| D _i | 20 mm | Inner diameter |
| D _o | 23 mm | Outer diameter |
| B | 30 mm | Width |
| C _r | 84.000 N | Basic dynamic load rating, radial |
| C _{0r} | 150.000 N | Basic static load rating, radial |
| ≈m | 22,12 g | Weight |



Dimensions

| | | |
|--------------------|-----------|-----------------------------------|
| f | 20 ° | Chamfer angle outside diameter |
| F _{iUT} | 0,1 mm | Inner edge break, lower tolerance |
| F _{iOT} | 0,7 mm | Inner edge break, upper tolerance |
| f | 0,6 mm | Outer chamfer |
| F _{i min} | 0,1 mm | Inner edge break, min. |
| F _{i max} | 0,7 mm | Inner edge break, max. |
| D _{iOT} | 0,061 mm | Inner diameter, upper tolerance |
| D _{oOT} | 0,075 mm | Outside diameter, upper tolerance |
| D _{iUT} | 0,001 mm | Inner diameter, lower tolerance |
| D _{oUT} | 0,035 mm | Outside diameter, lower tolerance |
| s ₃ | 1,5 mm | Wall thickness |
| s _{3OT} | 0,005 mm | Wall thickness, upper tolerance |
| s _{3UT} | -0,025 mm | Wall thickness, lower tolerance |
| B _{UT} | -0,25 mm | Width, lower tolerance |
| B _{OT} | 0,25 mm | Width, upper tolerance |
| f _{OT} | 0,4 mm | Outer chamfer, upper tolerance |
| f _{UT} | -0,4 mm | Outer chamfer, lower tolerance |
| F _i | 0,1 mm | Inner edge break |

Temperature range

| | | |
|------------------|---------|----------------------------|
| T _{min} | -200 °C | Operating temperature min. |
| T _{max} | 280 °C | Operating temperature max. |



Characteristics



Radial load



Lifetime lubrication, freedom from maintenance



Not sealed



Small design envelope