


Technical information



Your current product variant

Maintenance	Maintenance free
Type of Seal	Without Not sealed
Fabric	ELGOGLIDE
Material back	Steel

Main Dimensions & Performance Data

D _i	30 mm	Inner diameter
D _o	36 mm	Outer diameter
B	30 mm	Width
C _r	270.000 N	Basic dynamic load rating, radial
C _{0r}	270.000 N	Basic static load rating, radial
≈m	62,36 g	Weight



Dimensions

f	45 °	Chamfer angle bore diameter
f	15 °	Chamfer angle outside diameter
F _{iUT}	-0,2 mm	Inner edge break, lower tolerance
F _{iOT}	0,2 mm	Inner edge break, upper tolerance
f	1,5 mm	Outer chamfer
F _{i min}	0,2 mm	Inner edge break, min.
F _{i max}	0,6 mm	Inner edge break, max.
D _{iOT}	0,033 mm	Inner diameter, upper tolerance
D _{oOT}	0,051 mm	Outside diameter, upper tolerance
D _{iT}	H8	Inner diameter, tolerance
D _{oT}	p7	Outer diameter, tolerance
D _{iUT}	0 mm	Inner diameter, lower tolerance
D _{oUT}	0,026 mm	Outside diameter, lower tolerance
B _T	h12	Width tolerance
B _{UT}	-0,21 mm	Width, lower tolerance
B _{OT}	0 mm	Width, upper tolerance
f _{OT}	0,5 mm	Outer chamfer, upper tolerance
f _{UT}	-0,5 mm	Outer chamfer, lower tolerance
F _i	0,4 mm	Inner edge break

Temperature range

T _{min}	-50 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.



Characteristics



Radial load



Lifetime lubrication, freedom from maintenance



Not sealed



Small design envelope