

**EGF12070-E40-B**

## Flanged bush

Flanged bush, maintenance-free, ISO 3547,  
with bronze backing

## Technical information



## Your current product variant

Maintenance	Maintenance free
Material sliding Layer	E40 Maintenance-free sliding layer E40
Material back	Bronze

## Main Dimensions &amp; Performance Data

D <sub>i</sub>	12 mm	Inner diameter
D <sub>o</sub>	14 mm	Outer diameter
D <sub>f</sub>	20 mm	Outside diameter of flange
B	7 mm	Width
C <sub>r</sub>	8.400 N	Basic dynamic load rating, radial
C <sub>0r</sub>	15.000 N	Basic static load rating, radial
C <sub>a</sub>	15.800 N	Basic dynamic load rating, axial
C <sub>0a</sub>	28.300 N	Basic static load rating, axial
≈m	3,05 g	Weight



## Dimensions

f	20 °	Chamfer angle outside diameter
s <sub>fl</sub>	1 mm	Flange thickness
R <sub>max</sub>	1 mm	Radius, max.
f	0,6 mm	Outer chamfer
F <sub>i max</sub>	0,6 mm	Inner edge break, max.
F <sub>i min</sub>	0,1 mm	Inner edge break, min.
s <sub>3</sub>	1 mm	Wall thickness
D <sub>fl OT</sub>	0,5 mm	Outside diameter of flange, upper tolerance
D <sub>o OT</sub>	0,08 mm	Outside diameter, upper tolerance
s <sub>3 OT</sub>	0,005 mm	Wall thickness, upper tolerance
D <sub>fl UT</sub>	-0,5 mm	Outside diameter of flange, lower tolerance
s <sub>3 UT</sub>	-0,02 mm	Wall thickness, lower tolerance
D <sub>o UT</sub>	0,05 mm	Outside diameter, lower tolerance
B <sub>OT</sub>	0,25 mm	Width, upper tolerance
B <sub>UT</sub>	-0,25 mm	Width, lower tolerance
s <sub>fl OT</sub>	0,05 mm	Flange thickness, upper tolerance
s <sub>fl UT</sub>	-0,2 mm	Flange thickness, lower tolerance
f <sub>OT</sub>	0,4 mm	Outer chamfer, upper tolerance
f <sub>UT</sub>	-0,4 mm	Outer chamfer, lower tolerance

## Temperature range

T <sub>min</sub>	-200 °C	Operating temperature min.
T <sub>max</sub>	280 °C	Operating temperature max.



## Characteristics

---



Radial load



Axial load in one direction



Lifetime lubrication, freedom from maintenance



Not sealed



Protected against rust



Small design envelope