

**FAG****6021-C4**

Deep groove ball bearing

Deep groove ball bearing 60, single row, steel sheet metal cage

## Technical information

**Your current product variant**

Type of Seal	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Bore type	Z	Cylindrical

**Main Dimensions & Performance Data**

d	105 mm	Bore diameter
D	160 mm	Outside diameter
B	26 mm	Width
$C_r$	75.000 N	Basic dynamic load rating, radial
$C_{0r}$	64.000 N	Basic static load rating, radial
$C_{ur}$	3.550 N	Fatigue load limit, radial
$n_G$	5.700 1/min	Limiting speed
$n_{gr}$	4.950 1/min	Reference speed
$m$	1,67 kg	Weight



### Mounting dimensions

$d_{a \min}$	113,8 mm	Minimum diameter shaft shoulder
$D_{a \max}$	151,2 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
$D_1$	142,52 mm	Shoulder diameter outer ring
$d_1$	122,12 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Calculation factors

$f_0$	15,7	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed