

**FAG****6030-C3**

Deep groove ball bearing

Deep groove ball bearing 60, single row, steel sheet metal cage

## Technical information

**Your current product variant**

Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

**Main Dimensions & Performance Data**

d	150 mm	Bore diameter
D	225 mm	Outside diameter
B	35 mm	Width
$C_r$	131.000 N	Basic dynamic load rating, radial
$C_{0r}$	124.000 N	Basic static load rating, radial
$C_{ur}$	5.600 N	Fatigue load limit, radial
$n_G$	3.950 1/min	Limiting speed
$n_{gr}$	3.850 1/min	Reference speed
$m$	4,32 kg	Weight



### Mounting dimensions

$d_{a \min}$	160,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	214,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
$D_1$	201,42 mm	Shoulder diameter outer ring
$d_1$	174,36 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Calculation factors

$f_0$	16	Calculation factor
-------	----	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed