

**FAG****6003-2RSR-C4**

Deep groove ball bearing

Deep groove ball bearing 60...-2RSR, single row, seals, steel sheet metal cage

Technical information

**Your current product variant**

| | | |
|----------------------------------|--------------|---|
| Sealing | 2RSR | Contact seal on both sides |
| Cage | JN | Steel sheet metal |
| Tolerance class | PN | Normal (ISO 492:2023) |
| Dimensional / heat stabilization | SN | Rings dimensional stabilized up to 120° |
| Lubricant | GA14 | Ball bearing grease, low noise |
| Radial internal clearance | C4 (Group 4) | Internal clearance larger than C3 |
| Bore type | Z | Cylindrical |

Main Dimensions & Performance Data

| | | |
|-----------------|--------------|-----------------------------------|
| d | 17 mm | Bore diameter |
| D | 35 mm | Outside diameter |
| B | 10 mm | Width |
| C _r | 6.400 N | Basic dynamic load rating, radial |
| C _{0r} | 3.250 N | Basic static load rating, radial |
| C _{ur} | 162 N | Fatigue load limit, radial |
| n _G | 11.800 1/min | Limiting speed |
| m | 39,1 g | Weight |

Mounting dimensions

| | | |
|--------------------|--------|--------------------------------------|
| d _{a min} | 19 mm | Minimum diameter shaft shoulder |
| D _{a max} | 33 mm | Maximum diameter of housing shoulder |
| r _{a max} | 0,3 mm | Maximum fillet radius |



Dimensions

| | | |
|------------|----------|------------------------------|
| r_{\min} | 0,3 mm | Minimum chamfer dimension |
| D_1 | 29,51 mm | Shoulder diameter outer ring |
| D_2 | 30,81 mm | Caliber diameter outer ring |
| d_1 | 22,65 mm | Shoulder diameter inner ring |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -20 °C | Operating temperature min. |
| T_{\max} | 100 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|------|--------------------|
| f_0 | 14,3 | Calculation factor |
|-------|------|--------------------|

Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides