

**FAG****6008-2RSR-C3**

Deep groove ball bearing

Deep groove ball bearing 60..-2RSR, single row, seals, steel sheet metal cage

## Technical information



## Your current product variant

Sealing	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	40 mm	Bore diameter
D	68 mm	Outside diameter
B	15 mm	Width
C <sub>r</sub>	17.800 N	Basic dynamic load rating, radial
C <sub>0r</sub>	11.500 N	Basic static load rating, radial
C <sub>ur</sub>	600 N	Fatigue load limit, radial
n <sub>G</sub>	5.400 1/min	Limiting speed
m	0,189 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	44,6 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	63,4 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	1 mm	Maximum fillet radius



### Dimensions

$r_{min}$	1 mm	Minimum chamfer dimension
$D_1$	59,06 mm	Shoulder diameter outer ring
$D_2$	61,56 mm	Caliber diameter outer ring
$d_1$	49,3 mm	Shoulder diameter inner ring







### Temperature range

$T_{min}$	-20 °C	Operating temperature min.
$T_{max}$	100 °C	Operating temperature max.

### Calculation factors

$f_0$	15,2	Calculation factor
-------	------	--------------------

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides