

**FAG****6030-2RSR**

Deep groove ball bearing

Deep groove ball bearing 60...2RSR, single row, seals, steel sheet metal cage

## Technical information

**Your current product variant**

Type of Seal	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

**Main Dimensions & Performance Data**

d	150 mm	Bore diameter
D	225 mm	Outside diameter
B	35 mm	Width
C <sub>r</sub>	131.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	124.000 N	Basic static load rating, radial
C <sub>ur</sub>	5.600 N	Fatigue load limit, radial
n <sub>G</sub>	1.540 1/min	Limiting speed
m	4,3 kg	Weight

**Mounting dimensions**

d <sub>a min</sub>	160,2 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	214,8 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	2,1 mm	Maximum fillet radius



## Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
$D_1$	201,42 mm	Shoulder diameter outer ring
$D_2$	205,96 mm	Caliber diameter outer ring
$d_1$	173,9 mm	Shoulder diameter inner ring

## Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

## Calculation factors

$f_0$	16	Calculation factor
-------	----	--------------------

## Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides