

**FAG****6034-2RSR**

Deep groove ball bearing

Deep groove ball bearing 60...-2RSR, single row, seals, steel sheet metal cage

## Technical information

**Your current product variant**

Sealing	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

**Main Dimensions & Performance Data**

d	170 mm	Bore diameter
D	260 mm	Outside diameter
B	42 mm	Width
C <sub>r</sub>	179.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	172.000 N	Basic static load rating, radial
C <sub>ur</sub>	7.600 N	Fatigue load limit, radial
n <sub>G</sub>	1.340 1/min	Limiting speed
m	7,2 kg	Weight

**Mounting dimensions**

d <sub>a min</sub>	180,2 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	249,8 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	2,1 mm	Maximum fillet radius



## Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
$D_1$	231,4 mm	Shoulder diameter outer ring
$D_2$	236,45 mm	Caliber diameter outer ring
$d_1$	198,9 mm	Shoulder diameter inner ring

## Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

## Calculation factors

$f_0$	15,7	Calculation factor
-------	------	--------------------

## Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides