

**FAG****60/500-M**

Deep groove ball bearing

Deep groove ball bearing 60.-M, single row, solid brass cage

## Technical information



## Your current product variant

Type of Seal	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	500 mm	Bore diameter
D	720 mm	Outside diameter
B	100 mm	Width
C <sub>r</sub>	610.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	1.150.000 N	Basic static load rating, radial
C <sub>ur</sub>	28.500 N	Fatigue load limit, radial
n <sub>G</sub>	1.440 1/min	Limiting speed
n <sub>gr</sub>	1.070 1/min	Reference speed
m	132 kg	Weight



### Mounting dimensions

$d_{a \min}$	523 mm	Minimum diameter shaft shoulder
$D_{a \max}$	697 mm	Maximum diameter of housing shoulder
$r_{a \max}$	5 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	6 mm	Minimum chamfer dimension
$D_1$	659 mm	Shoulder diameter outer ring
$d_1$	574,85 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$f_0$	16,2	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing