

**FAG****6052-M-C3**

Deep groove ball bearing

Deep groove ball bearing 60...-M, single row,  
solid brass cage

## Technical information



## Your current product variant

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	260 mm	Bore diameter
D	400 mm	Outside diameter
B	65 mm	Width
$C_r$	310.000 N	Basic dynamic load rating, radial
$C_{0r}$	405.000 N	Basic static load rating, radial
$C_{ur}$	14.300 N	Fatigue load limit, radial
$n_G$	2.750 1/min	Limiting speed
$n_{gr}$	2.250 1/min	Reference speed
$m$	29,8 kg	Weight



### Mounting dimensions

$d_{a \min}$	274,6 mm	Minimum diameter shaft shoulder
$D_{a \max}$	385,4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
$D_1$	357,5 mm	Shoulder diameter outer ring
$d_1$	304,05 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$f_0$	15,7	Calculation factor
-------	------	--------------------

### Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Large bearing