

**FAG****6014-RSR**

Deep groove ball bearing

Deep groove ball bearing 60...RSR, single row, seal, steel sheet metal cage

Technical information

**Your current product variant**

Sealing	RSR	Contact seal on one side
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	70 mm	Bore diameter
D	110 mm	Outside diameter
B	20 mm	Width
C _r	40.500 N	Basic dynamic load rating, radial
C _{0r}	31.000 N	Basic static load rating, radial
C _{ur}	1.900 N	Fatigue load limit, radial
n _G	3.250 1/min	Limiting speed
≈m	0,613 kg	Weight

Mounting dimensions

d _{a min}	76 mm	Minimum diameter shaft shoulder
D _{a max}	104 mm	Maximum diameter of housing shoulder
r _{a max}	1 mm	Maximum fillet radius



Dimensions

r_{\min}	1,1 mm	Minimum chamfer dimension
D_1	97,28 mm	Shoulder diameter outer ring
D_2	100,04 mm	Caliber diameter outer ring
d_1	82,75 mm	Shoulder diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.

Calculation factors

f_0	15,6	Calculation factor
-------	------	--------------------

Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Sealed on one side