

**FAG****61848**

Deep groove ball bearing

Deep groove ball bearing 618, single row,  
steel sheet metal cage

## Technical information



## Your current product variant

Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	240 mm	Bore diameter
D	300 mm	Outside diameter
B	28 mm	Width
$C_r$	100.000 N	Basic dynamic load rating, radial
$C_{0r}$	124.000 N	Basic static load rating, radial
$C_{ur}$	4.500 N	Fatigue load limit, radial
$n_G$	2.900 1/min	Limiting speed
$n_{gr}$	2.260 1/min	Reference speed
$m$	3,93 kg	Weight



### Mounting dimensions

$d_{a \min}$	248,8 mm	Minimum diameter shaft shoulder
$D_{a \max}$	291,2 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
$D_1$	281,6 mm	Shoulder diameter outer ring
$d_1$	259,3 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$f_0$	15,9	Calculation factor
-------	------	--------------------

### Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed