

**FAG****61852-C3**

Deep groove ball bearing

Deep groove ball bearing 618, single row,
steel sheet metal cage

Technical information



Your current product variant

| | | |
|----------------------------------|--------------|---|
| Sealing | Without | Not sealed |
| Cage | JN | Steel sheet metal |
| Tolerance class | PN | Normal (PN) |
| Dimensional / heat stabilization | S1 | Rings dimensional stabilized up to 200° |
| Lubricant | Without | Bearing not greased |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Bore type | Z | Cylindrical |

Main Dimensions & Performance Data

| | | |
|-------------|-------------|-----------------------------------|
| d | 260 mm | Bore diameter |
| D | 320 mm | Outside diameter |
| B | 28 mm | Width |
| C_r | 102.000 N | Basic dynamic load rating, radial |
| C_{0r} | 132.000 N | Basic static load rating, radial |
| C_{ur} | 4.650 N | Fatigue load limit, radial |
| n_G | 2.700 1/min | Limiting speed |
| n_{gr} | 2.070 1/min | Reference speed |
| $\approx m$ | 4,338 kg | Weight |



Mounting dimensions

| | | |
|--------------|----------|--------------------------------------|
| $d_{a \min}$ | 268,8 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 311,2 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 2 mm | Maximum fillet radius |

Dimensions

| | | |
|------------|----------|------------------------------|
| r_{\min} | 2 mm | Minimum chamfer dimension |
| D_1 | 301,7 mm | Shoulder diameter outer ring |
| d_1 | 279,3 mm | Shoulder diameter inner ring |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 200 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|------|--------------------|
| f_0 | 15,8 | Calculation factor |
|-------|------|--------------------|

Characteristics

| | |
|---|------------------------------|
|  | Radial load |
|  | Axial load in one direction |
|  | Axial load in two directions |
|  | Grease Lubrication |
|  | Oil Lubrication |
|  | Not sealed |
|  | Large bearing |